

VEGATRONIC 2000OF

FLEXIBLE PACKAGING SOLUTIONS



MAIN FEATURES




- 1 • Top level intermittent film motion machine
- 2 • Hygienic Open Frame design
- 3 • Maximum versatility
- 4 • Extreme sealing pressure

BENEFITS

- 1 • Lowest cost of ownership and lowest cost per pack
- 2 • Easy monitoring for all machine components - Easy access maintenance
- Fast forming tube and film roll change over - Suitable for wash down IP65 areas with high sanitation requirements (IP66 optional)
- 3 • Wide range of pack styles (pillow, BB, Quattro, Flexcan, Easypack, Shark pouch) and seal options (different hang holes, TD zipper, clip, twist)
- 4 • Can handle thick films and guarantee tight seals for MAP applications

IMA Ilapak's Vegatronic 2000 Open Frame is today's most innovative and high-tech VFFS machine. It's a high-quality, high-end range machine with excellent sanitary design. Ideal to run a wide variety of pack styles including Doy shark packs and transverse zipper bags in industries such as Dairy, Bakery, Confectionery, Snacks and many others.

TECHNICAL DATA



	S	P	SP
Machine Speed	120 cpm	120 cpm	120 cpm
Wrapping Materials	Heat sealable materials, such as polypropylene, barrier films, laminates, polyethylene films, as well as paper based and recyclable films		
Sealing System*	Vertical seal bar Horizontal heat-seal jaw	laseal or llatherm jaws	Both S & P system
Electronic Platform	Commercial industrial PC with separate HMI and commercial I/O board for USA & Canada, Allen Bradley platform as an option		
Program Memory	100+ programs		
HMI	12" HMI colour touch screen TFT SVGA resolution		
Power Requirement	400 Vac+/-5%, 3 ph, neutral, GND, 50/60 Hz, 9.5 kW, 13 A		
Compressed Air	up to 125 l/min at 5 bar - 72,5 psi	up to 225 l/min at 5 bar - 72,5 psi	Same as per S or P
Machine Handing	Right hand version, left hand version		
Machine Dimensions	(Width x Depth x Height) 1930 x 2000 x 1710 mm - 76"x 79" x 67.25"		
Machine finish	Electrostatic epoxy powder coating- Stainless steel*		
Machine Weight	1400kg - 3100 lbs		
BAG SIZE	S	P	SP
length	580mm-22.8"	580mm-22.8"	580mm-22.8"
width min	50mm-2.0"	50mm-2.0"	50mm-2.0"
width max	420/430*mm-16.5/16.9**	410/420*mm-16.1/16.5**	Same as per S or P
FILM REEL DIMENSIONS	S	P	SP
Reel width man	880/930*mm-34.6/36.6**	880/930*mm-34.6/36.6**	880/930*mm-34.6/36.6**
reel outer ø max	550mm-21.6"	550mm-21.6"	550mm-21.6"
reel core ø max	76mm-3.0"	76mm-3.0"	76mm-3.0"
Film Reel Max Weight	100kg-220lbs	100kg-220lbs	100kg-220lbs

* Brushless motor driven horizontal sealing jaws-pneumatic vertical seal bar.