

STRETCH WRAPPER



CSA 965 STRETCH WRAPPER

The CSA 965 pallet wrapper can easily be integrated into an existing or new transport line. This wrapper ensures that the total costs in your production line will decrease due to the use of film with a high pre-stretch percentage. The CSA 965 is a maintenance-friendly machine, can wrap up to 65 pallets per hour and the film can easily be replaced by the fast-loading system. A corner mount can be added to the machine for extra strength.

Advantages

- Driven by a heavy-duty turntable with external gearing
- Pre-stretch 150% 200% 250%
- Handles up to 65 pallets per hour
- Wrapping speed 28 rpm
- Simple replacement of film roll with rapid-load system
- Weighted machine frame

Options

- Acid protection
- For loads up to 3000 mm high
- Pack stabiliser (pantograph)
- Corner applicator
- Clamp cut and tucking of the film tail inside the wrap
- Seal unit with contrastplate
- Topvel dispenser
- Pallet lifter
- Double film carriage
- Extended arm for bigger loads





Technical data	
Total power installed	3,5 Kw – 5,5 Kw with Top
Standard power supply	400 V - 50 Hz - 3 PH+N+G
Protection on electric system & motors	IP 54
Max. pallet diemensions	1200 x 1200 mm
Standard pallet height	2200 mm
Max. rotation speed	28 rpm
Max. capacity	Up to 65 pallets per hour
Operating presure	6 bar

